



CAMPANE INDUSTRIALI CARRELLATE  
INDUSTRIAL FLOOR MODELS  
CAMPANAS DE SOBREMESA  
MODÈLES SUR SOCLE INDUSTRIELS  
INDUSTRIELLE STANDMODELLE

INDUSTRIAL  
Sliding

**20** PROGRAMMI  
PROGRAMS  
PROGRAMAS  
PROGRAMMES  
PROGRAMME

- SOFT VACUUM  
- MARINATING FUNCTION  
- VACUUM SENSOR



STORM



CYCLON



BAYAMO



TYPHOON



HURRICANE

Dimensioni macchina Machine dimensions Dimensiones máquina Dimensions de la machine Maschinenabmessungen	1060 x 900 x 1179h mm	1260 x 1020 x 1185h mm	1483 x 1204 x 1341h mm	1900 x 1295 x 1450h mm	2420 x 1213 x 1597h mm
Peso   Weight   Peso   Poids   Gewicht	236 Kg	319 Kg	537 Kg	685 Kg	767 Kg
Voltaggio   Voltage   Voltaje   Tension   Spannung	400 V-3-50 Hz 220 V-3-60 Hz ●	400 V-3-50 Hz 220 V-3-60 Hz ●	400V-3-50 Hz 220V-3-60 Hz ●	400V-3-50 Hz 220V-3-60 Hz ●	400V-3-50Hz 220V-3-60Hz ●
Consumo   Consumption   Consumo   Consommation   Leistung	2,4-3,5 kW	3,0-5,0 kW	5,5-9,0 kW	7,0-9,0 kW	7,0-9,0 kW
Dimensioni camera   Chamber dimensions   Dimensiones cámara   Dimensions de la cuve   Kammergröße	(2x) 580x450x235 mm	(2x) 700x550x235 mm	(2x) 750x620x250 h mm	(2x) 830x840x255 h mm	(2x) 730x1100x280 h mm* 1000x850x280 h mm**
Pompa a bagno d'olio   Oil lubricated pump   Bomba de baño de aceite   Pompe à bain d'huile   Ölvakuumpumpe	63 m3/h Busch®	100 m3/h Becker®	160 m3/h Busch®	300 m3/h Busch®	300 m3/h Busch®
Barra saldante   Welding bar   Barra de soldadura   Barre de soudure   Schweißbalken	(2x) ☐ 450/450 mm ● ☐ 680/680 mm	(2x) ☐ 550/550 mm ●	(2x) ☐ 620/620 mm ● ☐ 840/840 mm	(2x) ☐ 840/840 mm ● ☐ 770/770 mm	(2x) ☐ 1100/1100 mm* ● ☐ 850/850 mm**
Barra taglio sfrido (opz.) ● Cut-off seal bar (opt.) Barra con corte de bolsa (opc.) Barre soudure coupure (opt.) Schweißbalken mit Abschneider (opt.)	●	●	●	●	●
Barra doppia saldatura ● Double seal bar Barra doble soldadura Barre double soudure Doppelschweißbalken	●	●	●	●	●
Atmosfera protettiva (opz.) Protective atmosphere (opt.) Atmósfera protegida (opc.) Atmosphère modifiée (opt.) Schutzatmosphäre (opt.)	●	●	●	●	●

● Prezzi disponibili su richiesta	Prices available on request	Precios disponibles bajo petición	Prix disponibles sur demande	Auf Anfrage erhältliche Preise
● Voltaggio speciale prezzo su richiesta	Special voltage price on demand	Voltaje especial precio a petición	Tension spéciale sur demande	Spezielle Spannung auf Anfrage
● Extra vuoto	Extra vacuum	Extra vacío	Vide supplémentaire	Extravakuum
● Opzioni non cumulabili	Non-cumulative options	Opciones no acumulativas	Options non cumulables	Nicht kombinierbare Optionen
● Di serie	Standard	Estándar	De série	Standard



CAMPANE INDUSTRIALI CARRELLATE  
 INDUSTRIAL FLOOR MODELS  
 CAMPANAS DE SOBREMESA  
 MODÈLES SUR SOCLE INDUSTRIELS  
 INDUSTRIELLE STANDMODELLE

INDUSTRIAL  
 Sliding

**20** PROGRAMMI  
 PROGRAMS  
 PROGRAMAS  
 PROGRAMMES  
 PROGRAMME

- SOFT VACUUM  
 - MARINATING FUNCTION  
 - VACUUM SENSOR



Sensore di vuoto ● Vacuum sensor Sensor de vacío Capteur de vide Vakuumsensor	●	●	●	●	●
Funzione marinatura ● Marinating function Funcion de marinado Fonction de marinade Marinierfunktion	●	●	●	●	●
Stampante (opz.) Printer (opt.) Impresora (opc.) Imprimante (opt.) Drucker (opt.)	●	●	●	●	●
Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) Troisième barre de soudure (opt.) Dritter Schweißbalken (opt.)	×	×	×	×	Su richiesta On demand Bajo pedido Sur demande Auf Anfrage