



TYPHOON

Dimensioni macchina Machine dimensions Dimensiones máquina Dimensions de la machine Maschinenabmessungen	1900 x 1295 x 1450h mm	Barra taglio sfrido (opz.) ● Cut-off seal bar (opt.) Barra con corte de bolsa (opc.) ● Barre soudure coupure (opt.) Schweißbalken mit Abschneider (opt.)
Peso Weight Peso Poids Gewicht	685 Kg	Barra doppia saldatura ● Double seal bar Barra doble soldadura ● Barre double soudure Doppelschweißbalken
Voltaggio Voltage Voltaje Tension Spannung	400V-3-50 Hz 220V-3-60 Hz ●	Atmosfera protettiva (opz.) Protective atmosphere (opt.) Atmosfera protegida (opc.) ● Atmosphère modifiée (opt.) Schutzatmosphäre (opt.)
Consumo Consumption Consumo Consummation Leistung	7,0-9,0 kW	Sensore di vuoto ● Vacuum sensor Sensor de vacío ● Capteur de vide Vakuumsensor
Dimensioni camera Chamber dimensions Dimensiones cámara Dimensions de la cuve Kammergröße	(2x) 830x840x255 h mm	Funzione marinatura ● Marinating function Funcion de marinado ● Fonction de marinade Marinierfunktion
Pompa a bagno d'olio Oil lubricated pump Bomba de baño de aceite Pompe à bain d'huile Ölvakuumpumpe	300 m3/h Busch®	Stampante (opz.) Printer (opt.) Impresora (opc.) ● Imprimante (opt.) Drucker (opt.)
Barra saldante Welding bar Barra de soldadura Barre de soudure Schweißbalken	(2x) ☐ 840/840 mm ● ☐ 770/770 mm	Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) Troisième barre de soudure (opt.) Dritter Schweißbalken (opt.) ×